



## 扁平電纜 Travelling Cable

227 IEC 71f (TVVB)型電纜綜合參數 227 IEC 71f (TVVB) Cable Parameter

型號電壓等級 Type Voltage class	導體截面 Conductor Section (mm <sup>2</sup> )	絕緣厚度 Type of Conductor (mm)	絕緣厚度 Thickness of Insulation (mm)			70℃時絕緣電阻 Insulator Resistance at 70℃ (MΩ km)	20℃時導體直流電阻 Conductor DC Resistance at 20℃ (Ω/km)	外形尺寸 Size (mm)	參考重量 Reference Weight (kg/km)
			e1	e2	e3				
227IEC71f (TVVB) 300/500V	3 × 0.75	0.6	1.0	0.9	1.5	≥ 0.011	≤ 26.0	11.0 × 4.5	83
	4 × 0.75	0.6	1.0	0.9	1.5	≥ 0.011	≤ 26.0	13.5 × 4.5	106
	5 × 0.75	0.6	1.0	0.9	1.5	≥ 0.011	≤ 26.0	16.0 × 4.5	125
	6 × 0.75	0.6	1.0	0.9	1.5	≥ 0.011	≤ 26.0	19.0 × 4.5	150
	9 × 0.75	0.6	1.0	0.9	1.5	≥ 0.011	≤ 26.0	27.5 × 4.5	219
	12 × 0.75	0.6	1.0	0.9	1.5	≥ 0.011	≤ 26.0	35.0 × 4.5	285
	16 × 0.75	0.6	1.0	0.9	1.5	≥ 0.011	≤ 26.0	45.5 × 4.5	375
	18 × 0.75	0.6	1.0	0.9	1.5	≥ 0.011	≤ 26.0	50.0 × 4.5	425
	20 × 0.75	0.6	1.0	0.9	1.5	≥ 0.011	≤ 26.0	56.0 × 4.5	470
227IEC71f (TVVB) 300/500V	3 × 1.0	0.6	1.0	0.9	1.5	≥ 0.010	≤ 19.5	11.5 × 4.7	100
	4 × 1.0	0.6	1.0	0.9	1.5	≥ 0.010	≤ 19.5	14.0 × 4.7	130
	5 × 1.0	0.6	1.0	0.9	1.5	≥ 0.010	≤ 19.5	17.0 × 4.7	155
	6 × 1.0	0.6	1.0	0.9	1.5	≥ 0.010	≤ 19.5	20.5 × 4.7	180
	9 × 1.0	0.6	1.0	0.9	1.5	≥ 0.010	≤ 19.5	29.0 × 4.7	260
	12 × 1.0	0.6	1.0	0.9	1.5	≥ 0.010	≤ 19.5	37.0 × 4.7	348
	16 × 1.0	0.6	1.0	0.9	1.5	≥ 0.010	≤ 19.5	48.5 × 4.7	455
	18 × 1.0	0.6	1.0	0.9	1.5	≥ 0.010	≤ 19.5	54.0 × 4.7	505
	20 × 1.0	0.6	1.0	0.9	1.5	≥ 0.010	≤ 19.5	60.0 × 4.7	560
227IEC71f (TVVB) 450/750V	3 × 1.5	0.7	1.0	1.0	1.5	≥ 0.010	≤ 13.3	13.0 × 5.3	129
	4 × 1.5	0.7	1.0	1.0	1.5	≥ 0.010	≤ 13.3	16.0 × 5.3	170
	5 × 1.5	0.7	1.0	1.0	1.5	≥ 0.010	≤ 13.3	19.0 × 5.3	210
	6 × 1.5	0.7	1.0	1.0	1.5	≥ 0.010	≤ 13.3	23.0 × 5.3	229
	9 × 1.5	0.7	1.0	1.0	1.5	≥ 0.010	≤ 13.3	33.0 × 5.3	330
	12 × 1.5	0.7	1.0	1.0	1.5	≥ 0.010	≤ 13.3	42.0 × 5.3	430
227IEC71f (TVVB) 450/750V	3 × 2.5	0.8	1.5	1.0	1.8	≥ 0.009	≤ 7.98	18.0 × 6.2	184
	4 × 2.5	0.8	1.5	1.0	1.8	≥ 0.009	≤ 7.98	19.5 × 6.2	250
	5 × 2.5	0.8	1.5	1.0	1.8	≥ 0.009	≤ 7.98	23.5 × 6.2	315
	6 × 2.5	0.8	1.5	1.0	1.8	≥ 0.009	≤ 7.98	28.5 × 6.2	335
	9 × 2.5	0.8	1.5	1.0	1.8	≥ 0.009	≤ 7.98	41.5 × 6.2	490
	12 × 2.5	0.8	1.5	1.0	1.8	≥ 0.009	≤ 7.98	53.0 × 6.2	645

電纜夾

